







del solution

LED Flood Light

Place an order: 514-992-7283

PRODUCT PHOTO	Item No.	VOLTAGE (V)	POWER (W)	Luminosity (Lm) ~6500K	Beam Angle	IP Grade	Net Weight	Size (mm)	Carton Size: cm	Gross weight / PCS per carton
	BG-731-W-10W	100-240 V/AC	10 W	850-900 Lm	120°	IP65	0.7 Kg	115*85*90 mm	29.5*29.5*28	7.5/8
	BG-731-S-10W		10 W	850-900 Lm	60°	IP65	0.7 Kg			
	BG-732-W-20W	100-240 V/AC	20 W	1700-1800 Lm	120°	IP65	1.5 Kg	180*140*120 mm	47*33*41	14.3/8
	BG-732-S-20W		20 W	1700-1800 Lm	60°	IP65	1.5 Kg			
	BG-732-W-30W	100-240 V/AC	30 W	2400-2600 Lm	120°	IP65	2.7 Kg	225*185*125 mm	57.5*37.5*27	12.8/4
	BG-732-S-30W		30 W	2400-2600 Lm	60°	IP65	2.7 Kg	225*185*125 mm		
	BG-733-W-40W	100-240 V/AC	40 W	3600-3800 Lm	120°	IP65	4.3 Kg	285*235*160 mm	67.5*39.5*31.5	19.3/4
	BG-733-W-50W		50 W	4000-4400 Lm	120°	IP65	4.5 Kg			
	BG-733-S-40W	100-240 V/AC	40 W	3600-3800 Lm	60°	IP65	4.3 Kg	285*235*160 mm	67.5*39.5*31.5	19.3/4
	BG-733-S-50W		50 W	4000-4400 Lm	60°	IP65	4.5 Kg			
	BG-736-W-60W	100-240 V/AC	60 W	5300-5500 Lm	120°	IP65	6.8 Kg	370*290*112 mm	45*32.5*35.5	15.2/2
	BG-736-W-70W		70 W	6200-6500 Lm	120°	IP65	6.8 Kg			
	BG-736-W-80W		80 W	7200-7500 Lm	120°	IP65	6.8 Kg			
	BG-736-W-90W		90 W	8100-8400 Lm	120°	IP65	6.8 Kg			
	BG-736-W-100W		100 W	8700-9000 Lm	120°	IP65	6.8 Kg			
	BG-736-S-60W	100-240 V/AC	60 W	5300-5500 Lm	60°	IP65	6.8 Kg	370*290*112 mm	45*32.5*35.5	15.2/2
	BG-736-S-70W		70 W	6200-6500 Lm	60°	IP65	6.8 Kg			
	BG-736-S-80W		80 W	7200-7500 Lm	60°	IP65	6.8 Kg			
	BG-736-S-90W		90 W	8100-8400 Lm	60°	IP65	6.8 Kg			
	BG-736-S-100W		100 W	8700-9000 Lm	60°	IP65	6.8 Kg			
	BG-745-W-60W	100-240 V/AC	60 W	5500-5800 Lm	120°	IP65	7.7 Kg	368*285*93 mm	46*34*42.5	17.5/2
	BG-745-W-80W		80 W	7100-7400 Lm		IP65	7.8 Kg			
	BG-745-S-60W	100-240 V/AC	60 W	5500-5800 Lm	60°	IP65	7.7 Kg	368*285*93 mm	46*34*42.5	17.5/2
	BG-745-S-80W		80 W	7100-7400 Lm		IP65	7.8 Kg			
	BG-742-W-160W	100-240 V/AC	160 W	12500-14000Lm	120°	IP65	15.9 Kg	552*397*172 mm	61*47*24	15.2/1
	BG-742-W-180W		180 W	14000-15500 Lm			15.9 Kg			
	BG-742-W-200W		200 W	15700-17200Lm			15.9 Kg			
	BG-742-S-160W	100-240 V/AC	160 W	12500-14000Lm	60°	IP65	15.9 Kg	552*397*172 mm	61*47*24	15.2/1
	BG-742-S-180W		180 W	14000-15500 Lm			15.9 Kg			
	BG-742-S-200W		200 W	15700-17200Lm			15.9 Kg			
	BG-746-W-100W	100-240 V/AC	100 W	8000-8500 Lm	120°	IP65	12.5 Kg	568*285*335 mm	67*35*29	13.5/1
	BG-746-W-120W		120 W	9500-10000 Lm			12.5 Kg			
	BG-746-W-150W		150 W	12000-12500 Lm			12.5 Kg			
	BG-746-S-100W	100-240 V/AC	100 W	8000-8500 Lm	60°	IP65	12.5 Kg	568*285*335 mm	67*35*29	13.5/1
	BG-746-S-120W		120 W	9500-10000 Lm			12.5 Kg			
	BG-746-S-150W		150 W	12000-12500 Lm			12.5 Kg			
	BG-747-W-180W	100-240 V/AC	180 W	14400-15500 Lm	120°	IP65	18.5 Kg	930*285*335 mm	99*38*28	20.3/1
	BG-747-W-200W		200 W	16000-17000 Lm			18.8 Kg			
	BG-747-S-180W	100-240 V/AC	180 W	14400-15500 Lm	60°	IP65	18.5 Kg	930*285*335 mm	99*38*28	20.3/1
	BG-747-S-200W		200 W	16000-17000 Lm			18.8 Kg			

