




del solution

LED Panel Light

Place an order: 514-992-7283

PRODUCT PHOTO	NO.	SIZE(mm)	VOLTAGE (V)	LED TYPE	POWER (W)	LED QTY.	LUMENS FLUX (Lm)(white)	COLOR	IP Grade	Accessory
	BG-513-10W	200X200 X12mm	AC 100-240	SAMSUNG 5630	10W	24 pcs	700 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-501-18W	300x300 X12mm	AC 100-240	SAMSUNG 5630	18W	48 pcs	1400 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-501-36W		AC 100-240		36W	96 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-507-18W	300X600 X12mm	AC 100-240	SAMSUNG 5630	18 W	44 pcs	1400 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-507-36W		AC 100-240		36 W	88 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-502-31W	300X900 X12mm	AC 100-240	SAMSUNG 5630	31 W	72 pcs	2500 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-503-36W	300x1200 X12mm	AC 100-240	SAMSUNG 5630	36 W	88 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-503-54W		AC 100-240		54 W	176 pcs	4300 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-503-72W		AC 100-240		72 W	176 pcs	5700 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-511-36 W	600x600 X12mm	AC 100-240	SAMSUNG 5630	36 W	88 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-511-48W		AC 100-240		48 W	110 pcs	3800 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-511-54W		AC 100-240		54 W	120 pcs	4300 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-511-72W		AC 100-240		72 W	176 pcs	5700 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-514-36 W	620x620 X12mm	AC 100-240	SAMSUNG 5630	36 W	96 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-514-54W		AC 100-240		54 W	120 pcs	4300 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-514-72W		AC 100-240		72 W	192 pcs	5700 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-515-36W	150x1200 X12mm	AC 100-240	SAMSUNG 5630	36 W	88 pcs	2900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-515-48W		AC 100-240		48 W	99 pcs	3800 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	
	BG-512-54W	600x1200 X12mm	AC 100-240	SAMSUNG 5630	54 W	176 pcs	4300 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	UL Driver
	BG-512-72W		AC 100-240		72 W	720 pcs	5700 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	







del solution

LED Panel Light

Place an order: 514-992-7283

PRODUCT PHOTO	NO.	SIZE(mm)	VOLTAGE (V)	LED TYPE	POWER (W)	LED QTY.	LUMENS FLUX (Lm)(white)	COLOR	IP Grade	Accessory
	BG-504	ø121*14.5 mm Hole: 4" ø108mm	AC 100-240	SMD3528	7W	40 pcs	420 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	CE Driver
	BG-506A	ø180*14.5 mm Hole: 6" ø170mm	AC 100-240	SMD3528	12W	50 pcs	750 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	CE Driver
	BG-508A	ø245*14.0 mm Hole: 8" ø225mm	AC 100-240	SMD3528	13 W	130 pcs	900 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	CE Driver
	BG-510A	ø278*14.5 mm Hole: 10" ø265mm	AC 100-240	SMD3528	17 W	210 pcs	1300 Lm	WW: 2700-3300K NW : 4000-4500K CW: 5500-6500K	IP50	CE Driver

PRODUCT PHOTO	NO.	SIZE(mm)	VOLTAGE (V)	LED TYPE	POWER (W)	LED QTY.	LUMENS FLUX (Lm)(white)	COLOR	IP Grade	Accessory
	BG-515	300x300 X12mm	AC 100-240V	SMD5050	8 W	30 pcs	/	R G B	IP50	 Adapted+RGBc ontroller
	BG-518	300x1200 X12mm	AC 100-240V	SMD5050	30 W	132 pcs	/	R G B	IP50	 Adapted+RGBc ontroller
	BG-519	600x600 X12mm	AC 100-240V	SMD5050	30 W	132 pcs	/	R G B	IP50	 Adapted+RGBc ontroller
	BG-520	600x1200 X12mm	AC 100-240V	SMD5050	48 W	198 pcs	/	R G B	IP50	 Adapted+RGBc ontroller







del solution

LED Panel Light

Place an order: 514-992-7283

Install photo	Description		Unit	Price per pc
	Suspend installation :	Accessories including: supporting wire, holder and hanging rings , screw	set	
			set	Only for 600*1200mm
	Wall installation :	Accessories including: 4 holder palte, screw	set	
	Frame installation :	Accessories including: Frame, screw		

